SERVICE BULLETIN

MITSUBISHI MOTORS

GLOBAL AFTER SALES OFFICE, MITSUBISHI MOTORS CORPORATION

PURPOSE : CHANGE	ISSUE NO. : MSB-14EXML00-002	DATE : 2014-01-17
SUBJECT : SPLASH SHIELD REMOVAL AND INSTALLATION & OVERFENDER REMOVAL AND INSTALLATION		<DESTINATION/MODEL> (As per attached sheet 1) <M/Y> 13-14
GROUP : GENERAL(Gr:00)		OUTLANDER/OUTLANDER PHEV(GF0W)

1. Description :

Please refer to the attached document for the information about the change of mention in the applicable service manual. (The grommet screw is used instead of the clip, and the splash shield mounting hole at the fender side is changed from the round hole(diameter:6mm) to the rectangle hole(8.5×8.5mm). Also, the moulding removal of both front and rear bumpers are amended.

2. Affected service manuals :

Please refer to the attached document (Attached sheet 1)

3. About the details :

Please refer to the attached document (Attached sheet 2 and 3(3/4-4/4))

4. Effective time :


1)The grommet screw / The splash shield mounting hole
13MY : From the vehicle produced in the end of Oct, 2013.
14MY & 14.5MY : From the vehicle produced initially.
2) The moulding removal of both front and rear bumpers
From the vehicle produced initially.

For overseas market Attached sheet 1


Destination	Application manual	Pub No.	Applicable title (INFO ID)	Contents
MMNA	2014 OUTLANDER Service manual CD-ROM	MSCD-007B-2014	SPLASH SHIELD REMOVAL AND INSTALLATION (M421-00-970-63600-01)	Attached sheet 2
EU/RUSSIA	2013 OUTLANDER Workshop manual	CGFE13E1-CD (ENG) CGFF13E1-CD (FRE) CGFG13E1-CD (GER) CGFS13E1-CD (SPA) CGFI13E1-CD (ITA) RUSSIA:N/A	SPLASH SHIELD REMOVAL AND INSTALLATION (M421-00-970-63600-01)	Attached sheet 2
EU/RUSSIA	2014 OUTLANDER PHEV Workshop manual	CGFE14E1-CD (ENG) CGFF14E1-CD (FRE) CGFG14E1-CD (GER) CGFS14E1-CD (SPA) CGFI14E1-CD (ITA) RUSSIA:N/A	SPLASH SHIELD REMOVAL AND INSTALLATION (M421-00-970-63600-01)	Attached sheet 2
EU/Russia/ ARGENTINA/ SOUTH AFRICA	2014 OUTLANDER Workshop manual	EUR/ARGENTINA/SOUTH AFRICA CGFE14E2-CD (ENG) CGFF14E2-CD (FRE) CGFG14E2-CD (GER) CGFS14E2-CD (SPA) CGFI14E2-CD (ITA) RUSSIA:N/A	OVERFENDER REMOVAL AND INSTALLATION (M511-02-470-58700-01)	Attached sheet 3
RUSSIA KD	2013 OUTLANDER Workshop manual (6B3)	N/A	SPLASH SHIELD REMOVAL AND INSTALLATION (M421-00-970-63600-01)	Attached sheet 2
MMAL/NZ/China	2013 OUTLANDER Workshop manual	MMAL:AU900304 NZ/CHINA:DRAFT	SPLASH SHIELD REMOVAL AND INSTALLATION (M421-00-970-64700-01)	Attached sheet 2
MMAL/NZ	2014.5 OUTLANDER Workshop manual	MMAL:AU900424 NZ:DRAFT	OVERFENDER REMOVAL AND INSTALLATION (M511-02-470-61700-01)	Attached sheet 3
G.EXP/GCC	2014 OUTLANDER Workshop manual	PWRE1303R(ENG) PWRS1304R(SPA)	SPLASH SHIELD REMOVAL AND INSTALLATION (M421-00-970-63600-01)	Attached sheet 2

Attached sheet 2

＜国内＞



＜For overseas market＞



＜国内＞


上図のようにクリップからグロメットスクリューへ変更すると共に，フェンダー側のスプラッシュシールド取付け穴を丸穴（Φ6）から四角穴（□8.5）に変更した。

＜For overseas market＞

As shown above, a grommet screw is used instead of the clip, and the splash shield mounting hole at the fender side is a rectangle hole (8.5×8.5 mm) in place of the round hole (diameter: 6 mm).


Attached sheet 3 (3/4)

Double-sided tape affixed location



Front wheel arch moulding

ACD03327



Rear wheel arch moulding

ACD03326

Double-sided tape: Generic products,
a: 25.0 mm width and 2.5 mm thickness
b: 20.0 mm width and 1.6 mm thickness
c: 4.0 mm width and 1.0 mm thickness
Specified primer: 3M K-500

ACD03509AB

Removal steps

- Side air dam (Refer to P.51-25.)

<<A>>
1. Front bumper moulding
2. Front bumper face pad

>>B<<
3. Front wheel arch moulding
4. Front overfender pad


>>A<<
5. Rear wheel arch moulding
6. Rear overfender pad

<<B>>
7. Rear bumper moulding
8. Rear bumper pad

REMOVAL SERVICE POINT

<<A>> FRONT BUMPER MOULDING REMOVAL

⚠ CAUTION



ACD03619AB

Note that the front wheel arch moulding and the front bumper moulding overlap.

<Old>


<New>

Insert A of the attached sheet 3(4/4).

<<B>> REAR BUMPER MOULDING REMOVAL

⚠ CAUTION

<Old>



ACD03618AB

Note that the rear wheel arch moulding and the rear bumper moulding overlap.

INSTALLATION SERVICE POINT


>>A<< REAR WHEEL ARCH MOULDING INSTALLATION

Application position of double-sided adhesive tape

Insert B of the attached sheet 3(4/4).


<New>

A



As the front wheel arch moulding and the front bumper moulding overlap, hold the front wheel arch moulding with hand when removing the front bumper moulding to prevent deformation.

B



As the rear wheel arch moulding and the rear bumper moulding overlap, hold the rear wheel arch moulding with hand when removing the rear bumper moulding to prevent deformation.