SERVICE BULLETIN

MITSUBISHI MOTORS

GLOBAL AFTER SALES OFFICE, MITSUBISHI MOTORS CORPORATION

PURPOSE : CORRECTION	ISSUE NO. : MSB-14E42-501	DATE : 2014-04-04
SUBJECT : CUSTOMISATION FUNCTION		<DESTINATION/MODEL> (EUR) <M/Y> 13-14
GROUP : KEYLESS OPERATION SYSTEM(Gr:42B)		MIRAGE/SPACE STAR/ATTRAGE

1. Description :

Please refer to the attached document for the correction of the error in writing existing in the applicable service manual.

2. Affected service manuals :

Applicable manual	Pub. No.	Applicable title (INFO ID)
2013 MIRAGE/SPACE STAR Workshop Manual	CA0E13E1-CD (Eng) CA0F13E1-CD (Fre) CA0G13E1-CD (Ger) CA0S13E1-CD (Spa) CA0I13E1-CD (Ita)	CUSTOMISATION FUNCTION (M429-61-161-05500-01)
2014 ATTRAGE/MIRAGE Workshop Manual	CA1E14E1-CD (Eng) CA1F14E1-CD (Fre) CA1G14E1-CD (Ger) CA1S14E1-CD (Spa) CA1I14E1-CD (Ita)	

3. About the details :

Please refer to the attached document (Attached sheet 1/2-2/2))

Attached sheet (1/2)

CUSTOMISATION FUNCTION

M1429611601055

Using the ETACS system of M.U.T.-III, the following functions can be programmed. The programmed information is held even when the battery is disconnected.

Adjustment item (M.U.T.-III display)	Adjustment item	Adjusting content (M.U.T.-III display)	Adjusting content
Hazard answer back	Adjustment of the number of keyless hazard warning lamp answer back flashes	Lock:1, Unlock:2	LOCK: Flashes once, UNLOCK: Flashes twice (Initial condition)
		Lock:1, Unlock:0	LOCK: Flashes once, UNLOCK: No flash
		Lock:0, Unlock:2	LOCK: No flash, UNLOCK: Flash twice
		Lock:2, Unlock:1	LOCK: Flash twice, UNLOCK: Flash once
		Lock:2, Unlock:0	LOCK: Flash twice, UNLOCK: No flash
		Lock:0, Unlock:1	LOCK: No flash, UNLOCK: Flash once
	<Deleted>	Lock:0, Unlock:0	No function
~~Auto fold mirror~~	~~Electric retractable mirror operation adjustment~~	~~Not Auto~~	~~No synchronised operation~~
		~~Open Vehicle SPD~~	~~Vehicle speed-dependent operation~~
		~~Open/Close by IG~~	~~Ignition switch linked operation~~
		~~OPN/CLS Keyless~~	~~Keyless entry linked operation~~ (Initial condition)
Door unlock (Shift "P" position)	Adjustment of the auto door unlock (P position) function	Disable	No function (Initial condition)
		Enable <Deleted>	Always with function
~~Buzzer answer back~~	~~Adjusts the buzzer answer back function. <vehicles with KOS>~~	~~Not Sound Buzzer~~	~~No function~~
		~~At KOS~~	~~Sounds when KOS is activated.~~ (Initial condition)
		~~At keyless~~	~~Sounds when the keyless entry system is activated.~~
		~~At Both~~	~~Sounds when the keyless entry system or KOS is activated.~~
~~Multi mode RKE~~	~~Multi-mode keyless entry function customisation~~	~~Disable~~	~~No function~~
		~~D-spec~~	~~Door mirror fold/unfold operation.~~ (Initial condition)
Timer lock timer	Timer lock period adjustment	30 sec.	30 seconds (Initial condition)
		60 sec.	60 seconds
		120 sec.	120 seconds
		180 sec.	180 seconds
KOS feature	KOS function adjustment	Both enable	All KOS functions are enabled. (Initial condition)
		Door Entry enable	Only door entry function is enabled.
		ENG start enable	Only engine starting function is enabled.
		Both disable	All KOS functions are disabled.

Adjustment item (M.U.T.-III display)	Adjustment item <Deleted>	Adjusting content (M.U.T.-III display)	Adjusting content
KOS unlock disable time	Adjusts the door unlock inhibition period after door lock is activated.	0 sec.	0 second
		3 sec.	3 seconds (Initial condition)
		5 sec.	5 seconds
Outer buzzer volume	Volume adjustment for the KOS outer buzzer	Volume 1	Quieter than the standard
		Volume 2	Standard volume (Initial condition)
		Volume 3	Louder than the standard

<Added>

KOS key detect out from window	With/without KOS key exterior detection function	Disable	No function (initial condition)
		Enable	With function